



Qingdao Maxx Auto Parts Co., Ltd

Qingdao Maxx Auto Parts Co., Ltd
Add: Dongchuan Road Qingdao 266041 China
Website: www.qdmaxx.cn
Email: maylu@qdmaxx.cn
Whatsapp/ Wechat / Facebook : +86 13864286305
Skype: May.Lu69



ABOUT US

Qingdao Maxx Auto Parts Company is one of the leading manufacturers of wheel accessories in China since 2012. Our production range is including:

- * Tire Valves for PCR, TBR, OTR
- * Wheel Balance Weight (Zinc, Steel, Lead)
- * Wheel nuts and Bolts
- * Wheel Spacers, Adapters, Hub Rings
- * Tire Repair Patch and Strings
- * Tire workshop tools and Equipment

We have established a strict quality control system. All the products are in a strict conformity to ISO/TS16949.

Currently, we export our goods to more than 50 countries in the world. We supply our goods to many retailers, wholesalers, tire manufacturers and car markers in the U.S.A, Europe, South America, South-east Asia, the Middle east and Africa. ect. Since our establishment in 2012, our sales have been increased year by year. We aim to have sales growth by at least 15% of each year.

We regard every customer as a reliable business partner. We believe that supporting each other is the only way to build a long-term business relationship. Our goal is to provide the best quality product at the lowest price and to deliver the best and the most professional service.

We will remain committed to delivering the world class service and we are the best choice for you.



CONTENTS

	TPMS Sensor Valve.....	3
Tire Valve	Tire Valve.....	4-9
	Tube Valve.....	10
	Valve Extender.....	11
	Valve Core / Cap/ Tool.....	12
Wheel Weight	Fe Adhesive Weights.....	13-14
	Fe Clip Weights.....	15
	Zn Clip Weights.....	16
	Pb Wheel Weight.....	17
Tire Patch	Tire Seal String & Kits.....	18
	Tire Combi/ Glue/ Mounting Paste.....	19
	Tire Patch.....	20-21
Lug Nuts & Adapter	Wheel Bolt.....	22
	Lug Nut.....	23-24
	Wheel Locks.....	25
	Wheel Spacer.....	26
	Wheel Adapter.....	27-28
	Hub Ring.....	29
Truck Tools	Truck Tools.....	30
Air Chuck & Gauge	Air Coupler & Chuck.....	31
	Tire Gauge.....	32
Cross Wrench & Impact Wrench	Wrench.....	33
Tire Changer & Balancer	Equipment.....	34-38



TPMS Valves



TPMS SERVICE KIT



Snap-in Tubeless Tire Valves

Caution

Maximum operating pressure(cold tyres): 4.5 bar check that rim holes are free from burrs and have a smooth, flat rust-free surface.

Rubber valves must be mounted on all rim types(aluminum or steel) having thickness of 1.8 min. at maxi 3.5 mm



Part No.	ETRTO No. (Ref.No)	Rim Hole Dia. (mm/in.)	Eff. Length (mm)	Parts		A	B	C
				Core	Cap			
TR412	V2.03.6	11.5/453"	22	9002#	VC8-BLACK	33	22	15
TR413	V2.03.1	11.5/453"	30			42.5	32	15
TR414	V2.03.2	11.5/453"	38			48.5	38	15
TR414L	V2.03.8	11.5/453"	45			56.5	46	15
TR418	V2.03.4	11.5/453"	49			61.5	51	15
TR423		11.5/453"	62			74	63.5	15
TR415	V2.03.3	16/625"	30			42.5	32	19.2
TR425		16/625"	49			61.5	51	19.2
TR438	V2.03.5	18.8/346"	32			40.5	31	11



Sleeve Snap-in Tubeless Valves





High Pressure Tubeless Tire Valves

Caution

TR600HP/602HP tubeless snap-in type valve for high pressure maximum cold inflation pressure is 5.5 bar

TR801HP/802HP tubeless snap-in type valve for high pressure maximum cold inflation 7 bar.



Part No.	Rim Hole Dia. (mm/in.)	Eff. Length (mm)	Parts	
			Core	Cap
TR600HP	11.5/ 453"	31	9002#	VC8-BLACK
TR602HP		50	9002#	VC8-BLACK
TR801HP	16/ 625"	33	9002#	VC8-BLACK
TR802HP		50	9002#	VC8-BLACK

Tubeless Metal Clamp-in Tire Valves

Caution

Valve torque: 5 to 6.1 N.M. You can grease the couple washer before mounting.



Parts No.	ETRTO No. (Ref. No.)	Rim Holes Dia. (mm/in.)	Eff. Length (mm)	Rubber Grommet	Washer	Nut	Cap
TR591B	WH402	11.5/ 453" 16/ 625"	19×34	RG39/RG54	RW8	HN4	AT
V-3	TR33E,WH23A	11.5/ 453"	14×33	HRG2×2	RW5	HN2×2	ET/BT
V-4	TR43E,WH206		14×43				
V-5	TR48E		14×48				
V-6	TR53E,WH204		14×43				
V-7	TR63E		14×63	HRG1,HG2	RW12		
V-8	TR34A		16×34				
VS-8	TR26G,PVR43A		16×38				
V-9	JS43E		16×43				
VS-8-45°	WH303,PVR75A		16×53-45°				DT
VS-8-90°			16×53-90°				
TR6008C	TRJF944	16/ 625"	17.5×34	RG39	RW8	HN4×2	ET/BT
PVR152		11.5/ 453"	16×65-90°	RG54	RW8	HN4	
PVR153		11.5/ 453"	17×70-90°	RG54	RW8	HN4	ET/BT
VS-6		6/ 236"	11×40				ET/BT
TR435		11.5/ 453"	19×34	RG54	RW8	HN4	

Tubeless Metal Clamp-in Tire Valves for Cars



Part No.	Ref. Length (mm)	Rim Holes	Parts				
			Rubber	Grommet	Washer	Nut	Cap
V2.04.1	17.5x35	11.5/.453"	V9.11.7			V9.7.1	FT
TR416	17x40	16/.625"	RG39		RW13	HN4	FT
TR416B	17x38/34	11.5/.453" 16/.625"	RG39 RG54		RW8	HN4	AT
TR416S	17x40	11.5/.453"	RG54		RW1	HN4	FT
TR416L	16.7x59	11.5/.453"	RG59		RW1	HN4	FT
TR416SS	14x38	11.5/.453"	V801		RW1	HN8	FT
TR416SSS	14x39	8.3/.327"	RG11		RW7	HN8	FT
MS525S	17.5x42	11.5/.453"	RG9 RG54		RW15	HN6	FT
MS525L	17.5x42	11.5/.453"	RG9 RG54		RW15	HN7	FT
MS525S	16x33	11.5/.453"	RG54		RW15	HN9	FT
MS525L	16x86/45"	11.5/.453"	RG4 RG6		RW5	HN4	ET

Tubeless Tire Valves for Motorcycles and Scooters





Tubeless Metal Clamp-in Tire Valves for Truck and Bus



Part No.	ETRTO No.	Ref. Length (mm)	Parts				
			Core	Rubber Grommet	Washer	Nut	Cap
TR500	V3.21.3	19×55	9002#	RG15	RW8	HN13	DT
TR501	V3.21.2	19×42	9002#	RG15	RW8	HN13	DT
TR502	64MS15.7	19×64	9002#	RG15	RW8	HN13	DT
TR570	V3.21.4	19×84	9002#	RG15	RW8	HN13	DT
TR571	V3.21.5	19×90	9002#	RG15	RW8	HN13	DT
TR572	V3.21.6	19×100	9002#	RG15	RW8	HN13	DT
TR573	V3.21.7	19×115	9002#	RG15	RW8	HN13	DT
TR574	V3.21.8	19×131	9002#	RG15	RW8	HN13	DT
TR575	V3.21.1	19×33	9002#	RG15	RW8	HN13	DT
TR570C	V3.21.9	19×84-90°27°	9002#	RG15	RW8	HN13	DT

European Style O-ring Seal Clamp-in Brass Tire Valves for Truck and Bus



Part No.	Ref. Length (mm)	Parts			
		Core	Rubber Grommet	Nut	Cap
V3.20.1	16×41	9002#	V9.115(RG60)	V9.07.2	DT
V3.20.2	16×95/17.50	9002#	V9.115(RG60)	V9.07.2	DT
V3.20.3	16×82	9002#	V9.115(RG60)	V9.07.2	DT
V3.20.4	16×90	9002#	V9.115(RG60)	V9.07.2	DT
V3.20.5	16×70	9002#	V9.115(RG60)	V9.07.2	DT
V3.20.6	16×115	9002#	V9.115(RG60)	V9.07.2	DT
V3.20.7	16×80	9002#	V9.115(RG60)	V9.07.2	DT
V3.20.8	16×119	9002#	V9.115(RG60)	V9.07.2	DT
V3.20.9	16×102	9002#	V9.115(RG60)	V9.07.2	DT
V3.20.10	16×80	9002#	V9.115(RG60)	V9.07.2	DT
150MS-27	16×150	9002#	V9.115(RG60)	V9.07.2	DT
DC1390	16×58	9002#	V9.115(RG60)	V9.07.2	DT

Air-liquid Tire Valves for Agricultural Tractors



Part No.	ETRTO No.	Ref. Length (mm)	Core Housing		Parts			
			Core	O-ring	Rubber Grommet	Washer	Nut	Cap
TRCH3	V4.02.1	11×36	9002#	HRG33 (V9.11.6)				DT
TRCH1		11×36						
TR618A	V5.01.1	22.5×30/510	TRCH3		RG7	RW11	HN1	
DVC601		22.5×56						
TR621A	V5.02.1	22.5×93/113/65°	9002#	HRG33 (V9.11.6)	RG7	RW11	HN1	DT
TR622A	V5.02.2	22.5×137/158/90°						
TR623A	V5.02.3	22.5×74/95/65°	TRCH3					

Large Bore Swivel Type Tire Valves



Part No.	Stem No.	EBRTO No.	A	B	α°
TRJ650-03	TRJ650-02	V5.04.1	27	79	80
TRJ651-03	TRJ651-02	V5.04.2	32	119	90
TRJ652-03	TRJ652-02		27	140	86
TRJ653-03	TRJ653-02		27	64	80
TRJ654-03	TRJ654-02		27	79	60
TRJ655-03	TRJ655-02		24	79	74
TRJ656-03	TRJ656-02		67	94	90
TRJ657-03	TRJ657-02		27	102	80
TRJ658-03	TRJ658-02		27	140	80
TRJ659-03	TRJ659-02		48	89	90
TRJ660-03	TRJ660-02		48	222	90
TRJ669-03	TRJ669-02		27	64	90

Air-liquid Tube Tire Valves




Part No.	Parts			
	Nuts	Core	Washer	Cap
SP4	HN2	9002#		VC8 or DT
SP6	HN1 HN11	9002#		
SP7		TRCH3	RW21	



European Style Clamp-in Valves




V3.12.1



V3.13.1

Part No.	Ref. Length (mm)	Parts			
		Grommet	Nut	Core	Cap
V3.12.1	26×21.5×40	V9.11.4	V9.13.1	9002#	CAP25
V3.12.2	26×21.5×95				

Part No.	Ref. Length(mm)			Parts			
	D	A	W	Grommet	Nut	Core	Cap
V3.13.1	46.5	42.5	153°	V9.11.4	V9.13.1	9002#	CAP25
V3.13.2	30	29	126°				



V3.14.1



V3.15.1

Part No.	Ref. Length(mm)			Parts			
	B	A	C	Grommet	Nut	Core	Cap
V3.14.1	26	21.5	24.5	V9.11.4	V9.13.1	9002#	CAP25
V3.14.2	45	21.5	24.5				

Part No.	Ref. Length(mm)			Parts			
	B	A	W	Grommet	Nut	Core	Cap
V3.15.1	14	22.5	110°	V9.11.2	V9.13.1	9002#	CAP25
V3.15.2	11	15.5	95°				



V3.16.1



V3.17.1

Part No.	Ref. Length(mm)			Parts			
	A	B	W	Grommet	Nut	Core	Cap
V3.16.1	36	29	150°	V9.11.4	V9.13.1	9002#	CAP25

Part No.	Ref. Length(mm)			Parts			
	B	A	W	Grommet	Nut	Core	Cap
V3.17.1	31.5	99	172°	V9.11.2	V9.13.1	9002#	CAP25
V3.17.2	31.5	116	172°				



V3.18.1



V3.19.1

Part No.	Ref. Length(mm)				Parts			
	B	D	E	W	Grommet	Nut	Core	Cap
V3.18.1	64	24.5	14.5	146°	V9.11.2	V9.13.1	9002#	CAP25
V3.18.2	81	24.5	14.5	146°				
V3.18.3	51	37.5	19.5	138°				
V3.18.3	51	37.5	19.5	138°				

Part No.	Ref. Length(mm)				Parts			
	B	D	E	W	Grommet	Nut	Core	Cap
V3.19.1	92	24.5	14.5	147°	V9.11.2	V9.13.1	9002#	CAP25
V3.19.2	76	24.5	15	145°				
V3.19.3	91	24.5	10	145°				
V3.19.3	91	24.5	10	145°				

Tube Valves



TR4



TR6



(TR NO.)	ETRTO NO.	EF.Length (mm)	Parts			
			Core	Washer	Cap	Cap
TR4(V1.09.1)	Z1-10-2(TZ5-33)	45x34	9002#	RW12 or YD6	HN2X2	VC8-E or VC8
TR6		68/42x34.5		YD6		
Z1-10-1	Z1-10-1(TZ5-30)	40x31		YD6	LM6 YM6	
Z1-10-3	Z1-10-3(TZ5-40)	50x41		YD5	LM5 YM5	
V1.06.1	V1.06.1	25x26/34			V9.03.2	



TR13



TR15

Part No.	ETRTO No. (Ref.No.)	Rim Hole	A	B	C	Core
TR13	V2.01.1	11.50mm/.453"	56mm	38mm	11.5mm	9003#
TR15	V2.01.2	16.00mm/.625"	56mm	38mm	16.00mm	9003#



TR218A



TR220A

(TR NO.)	ETRTO NO.	A	B	Core Housing	Lock Nut	Cap
TR218A	V4.01.1	27	65	TRCH3	TRLN10	VC618
TR218A	V4.01.2	27	95			
TR220A	V4.0102	35.5	63.5			



Valve Extensions



Part No.	Description	Length(mm)	Diameter(mm)
EX170R	Flexible rubber valve extension	75	12/10
EX100R		100	12/10
EX125R		125	12/10
EX150R		150	12/10
EX180R		180	12/10
EX210R		210	12/10
EX210R-VEH1		210	12/10
EX250R		250	12/10
EX270R		270	12/10
EX300R		300	12/10

Part No.	Description	Length(mm)	Diameter(mm)
EX64RM	Stainless steel braided rubber valve extension	65	12/10
EX125RM		125	12/10
EX150RM		150	12/10
EX180RM		180	12/10
EX210RM		210	12/10
EX250RM		250	12/10
EX300RM		300	12/10



Part No.	Description	Eff. Length(mm)	Total Length(mm)
EX51P	Plastic valve extension	33.5	51
EX71P		53.5	71
EX95P		77.5	95
EX115		97.5	115
EX125P		107.5	125
EX150P		132.5	150
EX170P		152.5	170
EX180P		162.5	180
EX200P		182.5	200

Part No.	Description	Eff. Length(mm)	Total Length(mm)
EX40M	Brass valve extension	34	40
EX60M		54	60
EX84M		78	84
EX8115M		100	115
EX125M		110	125
EX142M		127	142



Part No.	Eff. Length(mm)	Total Length(mm)
EX13M	13	21
EX19M	19	28
EX32M	32	41

Valve Cores



Valve Caps



Valve Tools





Lead free Fe Adhesive Wheel Weight

* Zinc Coated



Part # MX-FE1 (5gX12)



Part # MX-FE2 (5gX4+10GX4)



Part # MX-FE3 (5gX12)



Part # MX-FE4 (5gX4+10GX4)



Part # MX-FE5 (1/4 oz X12)



Part # MX-FE6 (1/2 oz*6)

* Plastic Coated



Part # MX-FE7 (5gX12)



Part # MX-FE8 (5gX4+10GX4)



Part # MX-FE9 (5gX12)



Part # MX-FE10 (5gX4+10GX4)



Part # MX-FE11 (1/4 oz X12)



Part # MX-FE12 (1/2 oz*6)

* Black Coated



Part # MX-FE13 (5gX12)



Part # MX-FE14 (5gX4+10GX4)



Part # MX-FE15 (5gX12)



Part # MX-FE16 (5gX4+10GX4)



Part # MX-FE17 (1/4 oz X12)



Part # MX-FE18 (1/2 oz*6)

*Tape Optional



Part # MX-FE19 (5g*1200)



Part # MX-FE20 (5g*1000)



Part # MX-FE21 (10g*12)



Part # MX-FE22 (20g*3)




Part # MX-FE23 (25g*6)



Part # MX-FE24 (28g*6)



Part # MX-FE25 (30g*5)



Part # MX-FE26 (50g*3)



Part # MX-FE27 (100g*2)

Truck

OZ



Fe Clip Wheel Weights For Steel & Alloy Rim

Zinc Clip Wheel Weights For Steel & Alloy Rim



Part# FN-FE
Size: (5g-60g) (0.25oz - 3oz)



Part# EN-FE
Size: (5g-60g) (0.25oz - 3oz)



Part# MC-FE
Size: (5g-60g) (0.25oz - 3oz)



Part# AW-FE
Size: (5g-60g) (0.25oz - 3oz)



Part# IAW-FE
Size: (5g-60g) (0.25oz - 3oz)



Part# P-FE
Size: (5g-60g) (0.25oz - 3oz)



Part# ST-FE
Size: (5g-60g)



Part# AL-FE
Size: (5g-60g)

P



Part# P-ZN
Size: 0.25oz - 3oz

MC



Part# MC-ZN
Size: 0.25oz - 3oz

AW



Part# AW-ZN
Size: 0.25oz - 3oz

FN



Part# FN-ZN
Size: 5gr-60gr

EN



Part# EN-ZN
Size: 5gr-60gr

T



Part# T-ZN
Size: 0.25oz - 3oz

Europe



Part# ST-ZN
Size: 5gr-60gr



Part# AL-ZN
Size: 5gr-60gr



Lead Wheel Weights For Cars



Part # PB-ST (5gr-60gr)




Part # PB-AL (5gr-60gr)



Part # PB-P (0.25 OZ-3OZ)



Part # PB-AW (0.25 OZ-3OZ)



Part # PB-1 (5gr*4+10gr*4)



Part # PB-1 (1/4oz*12)

Lead Wheel Weights For Trucks



Part # PB-3 (50gr, 100gr, 150gr, 200gr...400gr)



Part # PB-4 (25gr*4)



Part # PB-5 (50gr*4)

Tire Repair Plugs & Kits



Seal-1 (4''*3.5mm)



Seal-2 (8''*3.5mm)



TPR01



TPR02



Seal-3 (4''*6mm)



Seal-4 (8''*6mm)



TPR03



TPR04



TPR05



TPR06



TPR07



TPR08



TPR09



TPR10



Tire Repair Combi & European Style Patches



Combi Patch		Patch diameter mm	Pcs/box
Part No.	Stem Diameter/mm		
COMBI4	4	26	24
COMBI4L	4	36	24
COMBI6	6	36	24
COMBI6L	6	46	24
COMBI9	9	50	24
COMBI9L	9	60	24

Chemicals & USA Style Patches



CHEMICALS		Pcs/box
Part No.	Description	
VEM-250	VULCANIZING, 250 ML	40
VEM-500	VULCANIZING, 500 ML	20
BSL-250	BEAD SEALER, 250 ML	10
BSL-1000	BEAD SEALER, 1000 ML	40
PST-1	TIRE MOUNTING PASTE, 1 KG	8
PST-3	TIRE MOUNTING PASTE, 3 KG	4
PST-5	TIRE MOUNTING PASTE, 5 KG	2

European Style Patches

ITEM NO.	SIZE	PACKING	
EU-01	32mm	150pcs/box	32boxes/ctn
EU-02	42mm	100pcs/box	32boxes/ctn
EU-03	50mm	64pcs/box	36boxes/ctn
EU-04	75mm	36pcs/box	30boxes/ctn



ITEM NO.	SIZE	PACKING		PLY
BS80	80*80	15pcs/box	45boxes/ctn	1
BS100	100*100	10pcs/box	24boxes/ctn	2
BS128	128*128	15pcs/box	24boxes/ctn	2
BS170	170*170	10pcs/box	18boxes/ctn	3
BS220	220*220	5pcs/box	12boxes/ctn	6
BS260	260*260	5pcs/box	8boxes/ctn	6
BS295	295*295	5pcs/box	8boxes/ctn	6



ITEM NO.	SIZE	PACKING		PLY
EU46	46*68	20pcs/box	30boxes/ctn	1
EU55	55*75	20pcs/box	24boxes/ctn	1
EU70	70*120	10pcs/box	24boxes/ctn	1
EU82	82*130	10pcs/box	30boxes/ctn	1
EU74	75*100	10pcs/box	30boxes/ctn	2
EU85	85*135	10pcs/box	30boxes/ctn	2



5mm
4mm
3mm
Sticher 38-2mm



Scraper-B



Scraper-R



CP01



USA Style Patches

ITEM NO.	SIZE	PACKING
AP-01	35mm	50pcs/box 100boxes/ctn
AP-02	43mm	40pcs/box 100boxes/ctn
AP-03	58mm	30pcs/box 100boxes/ctn



ITEM NO.	SIZE	PACKING
AP-04	46mm	40pcs/box 100boxes/ctn
AP-05	56mm	30pcs/box 100boxes/ctn



ITEM NO.	SIZE	PACKING	PLY
AP100	100*100mm	10pcs/box 80boxes/ctn	1
AP135	135*135mm	10pcs/box 36boxes/ctn	2
AP165	165*165mm	10pcs/box 16boxes/ctn	2



ITEM NO.	SIZE	PACKING	PLY
RA75	75mm	20pcs/box 100boxes/ctn	1
RA90	90mm	10pcs/box 100boxes/ctn	1



ITEM NO.	SIZE	PACKING	PLY
RA65	65*80mm	20pcs/box 80boxes/ctn	1
RA80	80*120mm	10pcs/box 80boxes/ctn	1



Wheel Bolt





Lug Nut





Wheel Locks



4501



4601



4701



4801



4901



5001



5101



5201



5301

Wheel Spacer



SP000



SP001



SP002



SP003



SP004



SP005

Part#	THICKNESS	DESCRIPTION	I.D.	O.D.
SP000	3mm; 5mm; 8mm	4&5 Holes on 98-120mm	78mm	151mm
SP001	8mm	4 Holes on 98-120mm	71.5mm	151.5mm
SP002	8mm	5 Holes on 108-120mm	90mm	164.3mm
SP003	6mm	5&6 Holes on 5 1/2	107mm	178mm
SP004	6mm	8 Holes on 165.1mm	127mm	208mm
SP005	5mm; 8mm; 10mm	4&5 Holes on 98-120mm	78.5mm	145mm

Part#	THICKNESS	Bolt Pattern (mm)	Hub (mm)
SP100	10mm	5x120	72.6
SP101	15mm	5x120	72.6
SP102	20mm	5x120	72.6
SP103	25mm	5x120	72.6
SP104	30mm	5x120	72.6
SP105	10mm	5x120	74.1
SP106	15mm	5x120	74.1
SP107	20mm	5x120	74.1
SP108	25mm	5x120	74.1
SP109	30mm	5x120	74.1
SP110	10mm	5x112	66.6
SP111	15mm	5x112	66.6
SP112	20mm	5x112	66.6
SP113	10mm	5x112	57.1
SP114	15mm	5x112	57.1
SP115	20mm	5x112	57.1
SP116	25mm	5x112	57.1





Wheel Adapter

Part #	Thickness	Vehicle	Wheel	I.D.	Thread
AD100	15mm	4X100	4X100	60mm	M12X1.5
AD101	1"	4X100	4X4.5"	64mm	M12X1.5
AD102	1"	4X4.5"	4X4.5"	73mm	M12X1.5
AD103	1.25"	4X98	4X100	60mm	M12X1.5
AD104	1.25"	4X108	4X108	71mm	M12X1.5

4 Holes



Part #	Thickness	Vehicle	Wheel	I.D.	Thread
AD105	1"	5X100	5X100	60mm	M12X1.5
AD106	1"	5X4.5"	5X100	60mm	M12X1.5
AD107	1.25"	5X4.5"	5X4.5"	71mm	M12X1.5
AD108	1.25"	5X4.75"	5X4.75"	74mm	M12X1.5
AD109	1.25"	5X5"	5X5"	78mm	M12X1.5
AD110	1.25"	5X5"	5X135	78mm	M12X1.5
AD111	1.25"	5X5"	5X5"	78mm	M12X1.5
AD112	1.25"	5X135	5X135	87.1mm	1/2-20
AD113	1.25"	5X4.5"	5X4.75"	74mm	M12X1.5
AD114	1.25"	5X4.5"	5X5"	74mm	M12X1.5
AD115	1.25"	5X4.5"	5X135	78mm	M12X1.5
AD116	1.25"	5X4.5"	5X5"	78mm	M12X1.5
AD117	1.25"	5X4.25"	5X4.5"	71mm	M12X1.5
AD118	1.25"	5X4.75"	5X135	78mm	M12X1.5
AD119	1.25"	5X5.5"	5X5.5"	108mm	M12X1.5
AD120	1.25"	5X5.5"	5X135	87.1mm	M12X1.5
AD121	1.25"	5X130	5X130	71.6mm	M12X1.5
AD122	1.25"	5X120	5X112	71mm	M12X1.5
AD123	1.25"	5X108	5X108	71mm	M12X1.5
AD124	1.25"	5X108	5X4.5"	71mm	M12X1.5
AD125	15mm	5X114.3	5X114.3	73mm	M12X1.5
AD126	20mm	5X100	5X100	60mm	M12X1.5
AD127	30mm	5X150	5X150	110mm	M12X1.5
AD128	30mm	5X165.1	5X165.1	125mm	M12X1.5

5 Holes



6 Holes



Part #	Thickness	Vehicle	Wheel	I.D.	Thread
AD129	1.25"	6X5.5"	6X5.5"	110mm	M14X1.5
AD130	1.25"	6X5"	6X5.5"	87.1mm	M12X1.5
AD131	1.25"	6X5"	6X4.5"	74mm	M12X1.5
AD132	1.5"	6X135	6X5.5"	87.1mm	M12X1.5
AD133	1.5"	6X4.5"	6X4.5"	71mm	M12X1.5

Part #	Thickness	Vehicle	Wheel	I.D.	Thread
AD134	1.5"	8X170	8X170	126.65mm	M14X1.5
AD135	2"	8X6.5"	8X6.5"	125mm	9/16-18
AD136	2"	8X200	8X200	145mm	M14X1.5
AD137	2.5"	8X170	8X6.5"	125mm	M14X1.5
AD138	3"	8X6.5"	8X170	125mm	M14X1.5

8 Holes




Part #	Thickness	Vehicle	Wheel	I.D.	Thread
AD139	1"	4X100/4.25"	4X100	71mm	M12X1.5
AD140	1"	4X100/4.25"	4X4.5"	71mm	M12X1.5
AD141	1"	4X100/4.5"	4X4.5"	71mm	M12X1.5
AD142	1"	4X108/4.5"	4X100	71mm	M12X1.5
AD143	1"	5X100/112	5X4.5"	71mm	M12X1.5
AD144	1.25"	5X100/4.25"	5X4.5"	71mm	M12X1.5
AD145	1.25"	5X108/4.5"	5X4.75"	71mm	M12X1.5
AD146	1.25"	5X4.5"/4.75"	5X5.5"	78mm	M12X1.5
AD147	1.25"	5X4.5"/4.75"	5X135	78mm	M12X1.5
AD148	1.25"	5X4.5"/4.75"	5X4.5"	78mm	M12X1.5
AD149	1.25"	5X4.5"/4.75"	5X5"	74mm	M12X1.5
AD150	1.25"	5X4.5"/4.75"	5X112	74mm	M12X1.5
AD151	1.25"	5X4.5"/4.75"	5X4.75"	74mm	M12X1.5
AD152	1.25"	5X4.5"/5.5"	5X4.75"	78mm	M12X1.5
AD153	1.25"	5X5"/5.5"	5X135	87.1mm	M12X1.5
AD154	1.25"	5X5"/135	5X135	78mm	M12X1.5
AD155	1.25"	5X5"/4.75"	5X4.5"	78mm	M12X1.5
AD156	1.25"	5X5"/4.75"	5X4.75"	78mm	M12X1.5
AD157	1.25"	5X5"/4.75"	5X5"	78mm	M12X1.5
AD158	1.5"	5X5"/4.75"	5X135	78mm	M12X1.5
AD159	1.5"	5X135/5.5"	5X135	87.1mm	M12X1.5
AD160	1.5"	5X135/5"	5X5.5"	87.1mm	M12X1.5
AD161	1.5"	5X135/5"	5X4.5"	78mm	M12X1.5
AD162	1.5"	5X135/5"	5X4.75"	78mm	M12X1.5
AD163	1.5"	5X5.5"/4.5"	5X5.5"	78mm	M12X1.5
AD164	1.5"	5X5.5"/4.75"	5X4.75"	78mm	M12X1.5
AD165	1.5"	5X5.5"/135	5X4.5"	78mm	M12X1.5
AD166	1.5"	6X5"/135	5X5.5"	87.1mm	M12X1.5

Dual Drill





Aluminum & Plastic Hub Rings



OD	ID
60.1-54.1	
60.1-56.1	
60.1-56.6	
60.1-57.1	
60.1-58.1	
63.4-54.1	
63.4-56.1	
63.4-56.6	
63.4-57.1	
63.4-58.1	
63.4-59.1	
64-54.1	
64-56.1	
64-56.6	
64-57.1	
64-58.1	
64-59.1	
64-60.1	
67.1-54.1	
67.1-56.1	
67.1-56.6	
67.1-57.1	
67.1-58.1	
67.1-58.6	
67.1-59.1	
67.1-60.1	

OD	ID
67.1-63.4	
67.1-64.1	
67.1-66.1	
70.1-54.1	
70.1-56.1	
70.1-56.6	
70.1-57.1	
70.1-58.1	
70.1-59.1	
70.1-60.1	
70.1-63.4	
70.1-65.1	
70.1-66.6	
72.6-54.1	
72.6-56.1	
72.6-56.6	
72.6-57.1	
72.6-59.2	
72.6-59.6	
72.6-60.1	
72.6-63.4	
72.6-63.9	
72.6-64.1	
72.6-65.1	
72.6-66.1	
72.6-66.6	

OD	ID
72.6-67.1	
72.6-70.1	
72.6-70.3	
72.6-70.5	
73.1-54.1	
73.1-56.1	
73.1-56.6	
73.1-57.1	
73.1-58.1	
73.1-58.8	
73.1-59.1	
73.1-59.6	
73.1-60.1	
73.1-63.4	
73.1-63.5	
73.1-63.9	
73.1-64.1	
73.1-65.1	
73.1-66.1	
73.1-66.6	
73.1-67.1	
73.1-70.1	
73.1-70.3	
73.1-70.5	
73.1-71.5	
74-54.1	

OD	ID
74-56.1	
74-56.6	
74-57.1	
74-58.1	
74-59.1	
74-60.1	
74-63.4	
74-63.9	
74-64.1	
74-65.1	
74-66.1	
74-66.6	
74-67.1	
74-70.1	
74-70.3	
74-71.5	
74-72.6	
78.1-66.1	
78.1-66.56	
78.1-70.3	
78.1-71.5	
78.1-72.56	
78.1-74.1	
87.1-78.1	
108-78.1	
108-100	

Truck Tools



CH1 (5, 8, 10 Gallon)



CH2 (8 Gallon)



CH3 (10 Gallon)



TDT-1



TDT-2



TDT-3



TW-1



TL-1



TL-2

TL-3



Air Coupler Set 5pcs



AC-B (Brass)



AC-I (Iron)

Air Chuck



AC01



AC02



AC03



AC04



AC05



AC06



AC07



AC08



AC09



AC10



AC11



AC12



AC13



AC14



AC15

Gauges



PG01



PG02



PG03



PG04



PG05



PG06



PG07



PG08



PG09



PG10



TDG01



TDG02



PCD01

Eccentric Bolt



EB1(10# 12# Single Washer)

EB2(10, 12, 13, 14, 14.2, 15, 16, 17 Double Washer)



Wrench



HW01



HW02



HW03



HW04



HW05



HW06



HW07



IW1 (1/2")



IW2 (1/2")



IW3 (1")

Equipment



STC868R

Voltage: 110V/220V/380V
Dismount wheel width: 3-14"
Motor power 1.1kw/0.75kw
Maximum wheel diameter 1180mm
Inside clamp size 15" ~ 28"
Outside clamp size 12" ~ 26"



STC978

Voltage: 220V/380V
Working pressure: 8-10bar
Motor power: 0.75kw-1.1kw
Card axis revolution: 6.5r/min
Bead breaker running speed: 3S
Removable rim Diameter: 1180
Dismount tire width: 155mm-410mm/6"-16"



S909



S828



STC758



Equipment



SXJS4023

1. Lifting Capacity: 4.0 Ton/8818LB
2. Min Height: 290mm/11in
3. Lifting Height: 1900mm/75in
4. Platform Length: 4500mm/177in
5. under Ground Installation, with optional ramps for ground surface installation
6. Wheel Alignment Function



SXJS3018

1. Lifting Capacity: 3.0 Ton/6614LB
2. Under Ground Installation
3. Min Height: 340mm/13in
4. Lifting Height: 1800mm/71in
5. Platform Length: 1560-1760mm/61-70in



G6T (3D Wheel Aligner)

1. Electric movable Beam;
 2. Automatic tracking cameras with 1.3 million pixel;
 3. 4-point clamps
 4. 32" LCD TV
 5. With a small movable cabinet
 6. with 7 extension functions
- Database from AUTODATA in UK is optional.



QJ-Y-2-40C

1. Lifting Capacity: 4.0 Ton/8818LB
2. Electric Release
3. Front 2-step + Rear 3-step Extension Arms
4. Min Height: 100mm/4in
5. Lifting Height: 1900mm/74in
6. Total Height: 3900mm/154in
7. With Plunger Type Cylinder

Truck Equipment

T568

- Power: 220/380V 50/60HZ 1P/3P Optional
Rim Diameter: 14"-26"
Max. wheel weight: 500kgs
Max. tire diameter: 1600mm
Max tire width: 780 mm
Hydraulic pump motore: 1.5KW 380V-3ph (220V Optional)
Gearbox motor 1.8kw 380V-3ph (220V Optional)
Bead breaker fore: 2500kg
Operation control voltage : 24V



T-998A

- Power: 400V HZ 3P Optional
Rim Diameter: 14"-60"
Max. wheel weight: 2000kgs
Max. tire diameter: 2600mm
Max tire width: 1400 mm
Hydraulic pump motore: 3.3/4.0KW
Gearbox motor 2.4/3.0kw



CB1200

- Power supply: 400V/220V optional
Rim diameter: 13"-24"
Rim width: 5.5-20"
Max. wheel weight: 150kgs
Max. tire diameter: 1200mm
Air pressure: 6-8 bar
Testing time: 8s
Protection cover: supplied
Pneumatic built-in lift: supplied

Equipment



MX-E

Electric tire changer
Applicable tyre: R17.5, R19.5 R22.5 All series tyres
Weight: 130kgs
Electric Voltage: 220V/380V
Speed: 6 times/min
Voltage and power: 4KW



MX-A

Air powered tire changer
Applicable tyre: R22.5 All series tyres
Working pressure: 0.8-1.2Mpa
Weight: 95kgs
Speed: 5 times/min



T003



T004



T005



T006



T007



T008



T001



T002



T009



T010



T011